


Scan 



ST10 FX

6-10 ton machines

The ST10 FX, suitable for carriers of 6-10 tons, adds incredible flexibility to any midsize excavator. With its endless rotation, 45° of tilting and optional gripper, the tiltrotator enables operators to tackle more complex jobs, without having to reposition the excavator – saving time, fuel and money. The new hydraulic distribution block has been optimized to reduce energy consumption.

Equipped with a new built-in encoder, the tiltrotator can be integrated with machine guidance or control systems, enabling more efficient and precise operation. The tiltrotator can be mounted on the excavator directly or on a quick coupler.

* Read more on smpparts.com

SPECIFICATIONS


- Available with S45 Safelock, S50 Hardlock or FC45 Open-S couplers. Other quick coupler systems available on demand
- Tilt angle up to 45°
- Endless rotation
- Rotation sensor included on MACS control systems
- Central lubrication as standard
- Load holding valves on cylinders, for maximum safety
- Optional telescopic cylinders, reducing the total width
- Optional gripper, with exceptionally wide opening

CONTROL SYSTEMS

Available with SVAB's MACS control system, MIC4.0 or 4-hose solutions. Other systems available on request.

ELECTRICAL SYSTEM

For 12V or 24V systems.



SPECIFICATIONS	ST10 FX
Dimension A (mm)*	870
Dimension B (mm)*	590
Dimension C (mm)*	504
Dimension D (mm)*	600
Tilt angle max (°)	45
Weight from (kg)	310
Max breakout force (kNm)	70
Flow extra outlet (l/min)	60-65
Typ	Grip
Weight (kg)	83
Opening width (mm)	650

Dimensions, weights and tilt angle may vary depending on the configuration.