

Scan



# ST22 FX

16-22 ton machines

The ST22 FX is a slightly larger but equally precise tiltrotator for excavators of 16-22 tons. Improved hydraulics include a pressure relief valve directly on the motor, load holding valves on the cylinders, and a single hydraulic distribution block for improved efficiency.

Available now with a high flow swivel, optimized for use with attachments requiring up to 200l/min of flow. An innovative electric swivel can be added for further flexibility, enabling the transmission of sensor or CAN signals.

Equipped with a new built-in encoder, the tiltrotator can be integrated with machine guidance or control systems, enabling more efficient and precise operation.

\* Read more on [smpparts.com](http://smpparts.com)

## SPECIFICATIONS


- Available with S60-70 Hardlock or FC60-70 Open-S couplers. Other quick coupler systems available on demand
- Tilt angle up to 45°
- Endless rotation
- Rotation sensor included on MACS control systems
- Central lubrication as standard
- Load holding valves on cylinders, for maximum safety
- Optional telescopic cylinders, reducing the total width
- Optional gripper, with exceptionally wide opening

## CONTROL SYSTEMS

Available with SVAB's MACS control system, MIC4.0 or 4-hose solutions. Other systems available on request.

## ELECTRICAL SYSTEM

For 24V systems.



SPECIFICATIONS	ST22 FX
Dimension A (mm)*	1000
Dimension B (mm)*	830
Dimension C (mm)*	623
Dimension D (mm)*	830
Tilt angle max (°)	45
Weight from (kg)	628
Max breakout force (kNm)	150
Flow extra outlet (l/min)	60-65
High flow NG10 (l/min)	120
High flow "bypass" (l/min)	200
Typ	Grip
Weight (kg)	117/122 (S60/70)
Opening width (mm)	900

*Dimensions, weights and tilt angle may vary depending on the configuration.*