

Scan



ST28 FX

22-28 ton machines

The ST28 FX is the largest tiltrotator, suitable for excavators of 22-28 tons. Improved hydraulics include a pressure relief valve directly on the motor, load holding valves on the cylinders, and a single hydraulic distribution block for improved efficiency.

Available now with a high flow swivel, optimized for use with attachments requiring up to 200l/min of flow. An innovative electric swivel can be added for further flexibility, enabling the transmission of sensor or CAN signals.

Equipped with a new built-in encoder, the tiltrotator can be integrated with machine guidance or control systems, enabling more efficient and precise operation.

* Read more on smpparts.com

SPECIFICATIONS


- Available with S70 Hardlock or FC70 Open-S couplers. Other quick coupler systems available on demand
- Up to 45 degrees of tilting
- Endless rotation
- Rotation sensor included on MACS control systems
- Central lubrication as standard
- Load holding valves on cylinders, for maximum safety
- Optional telescopic cylinders, reducing the total width
- Optional gripper, with exceptionally wide opening

CONTROL SYSTEMS

Available with SVAB's MACS control system, MIC4.0 or 4-hose solutions. Other systems available on request.

ELECTRICAL SYSTEM

For 24V systems.



SPECIFICATIONS	ST28 FX
Dimension A (mm)*	1080
Dimension B (mm)*	1020
Dimension C (mm)*	670
Dimension D (mm)*	860
Tilt angle max (°)	45
Weight from (kg)	770
Max breakout force (kNm)	180
Flow extra outlet (l/min)	60-65
High flow NG10 (l/min)	120
High flow "bypass" (l/min)	200
Typ	Grip
Weight (kg)	122
Opening width (mm)	900

Dimensions, weights and tilt angle may vary depending on the configuration.